

US008475627B2

US 8.475.627 B2

*Jul. 2, 2013

(12) United States Patent

van Heiningen et al.

(54) PROCESS OF TREATING A LIGNOCELLULOSIC MATERIAL

(75) Inventors: Adriaan Reinhard Pieter van

Heiningen, Orono, ME (US);

Sung-Hoon Yoon, Old Town, ME (US); Haixuan Zou, Orono, ME (US); Jianer Jiang, Mason, OH (US); Gopal C.

Goyal, Mason, OH (US)

(73) Assignees: University of Maine System Board of

Trustees, Bangor, ME (US); International Paper Company,

Memphis, TN (US)

(*) Notice: Subject to any disclaimer, the term of this

patent is extended or adjusted under 35

U.S.C. 154(b) by 0 days.

This patent is subject to a terminal dis-

claimer.

(21) Appl. No.: 13/108,239

(22) Filed: May 16, 2011

(65) **Prior Publication Data**

US 2011/0214826 A1 Sep. 8, 2011

Related U.S. Application Data

- (63) Continuation of application No. 12/649,614, filed on Dec. 30, 2009, now Pat. No. 7,943,009, which is a continuation of application No. 11/640,820, filed on Dec. 18, 2006, now Pat. No. 7,824,521.
- (51) **Int. Cl. D21C 1/06**

(2006.01)

(52) **U.S. Cl.**

USPC **162/43**; 162/9; 162/17; 162/41

(58) Field of Classification Search

USPC 162/9, 19, 41, 43, 90, 17 See application file for complete search history.

(10) **Patent No.:**

(56)

(45) Date of Patent:

References Cited U.S. PATENT DOCUMENTS

2,904,460 A 9/1959 Nolan 3,354,029 A 11/1967 Hartler et al.

(Continued)

FOREIGN PATENT DOCUMENTS

CA 2368872 10/2000 WO 9500698 A1 1/1995 WO 2006134126 A1 12/2006

OTHER PUBLICATIONS

Grace editor, Pulp and Paper Manufacture: Alkaline Pulping, 1989, The Joint Textbook Committee of the Paper Industry, vol. 5 3rd edition, p. 68-71.*

(Continued)

Primary Examiner — Anthony Calandra (74) Attorney, Agent, or Firm — MacMillan, Sobanski & Todd, LLC

(57) ABSTRACT

A process of treating a lignocellulosic material includes a pre-extraction step in which hemicellulose is extracted from the lignocellulosic material. In one embodiment, the pre-extraction step involves contacting the lignocellulosic material with an aqueous solution under conditions that release acidic material from the lignocellulosic material into the aqueous solution, and the aqueous solution includes a basic material that at least partly neutralizes the acidic material so that the aqueous solution at the end of the pre-extraction step has a pH within a range of from 4.5 to 11. The process also includes a pulping step, after the pre-extraction step, in which the lignocellulosic material is separated into pulp. The process further includes an adsorption step, after the pulping step, in which hemicellulose is adsorbed on the pulp.

14 Claims, 11 Drawing Sheets

